

FLOW REGULATOR MODEL SUDFR BROCHURE



Flow Regulator Model SUDFR

SUDFR (1/4", 3/8", 1/2", 3/4", 1")

FEATURES

- Shavo's Uni-directional Flow Regulator unit for process control is specifically designed as high performance product for instrument air use in severe atmosphere.
- A typical application is the speed control of an actuator.
- CE, ATEX, EAC Ex(CUTR-12), EAC (CUTR-10) approved.
- Suitable for the applications include marine environment, oil and gas productions, chemicals and food processing, medical analysis, corrosive atmosphere etc.
- All External parts are NACE MR 0175* approved.

(*National Association of Corrosion Engineers MR-0175 defines requirements for sulphide stress cracking resistant materials used in oilwells and corrosive environments).

PARAMETERS	SPECIFICATIONS
Fluid / Operating Media	Compressed Air Gases - Filtered lubricated or non-lubricated air, inert gas, sweet (Natural) gases. Liquids - Low pressure hydraulic, mineral oil or water
Pipe size/ Connections	1/4", 3/8", 1/2", 3/4", 1".
Pipe Thread	NPT - Standard BSPT, BSP - Optional
Max. Working Pressure	12 bar (174 psi) maximum.
Material of Construction Body, bonnet, internals Spring Seals (Elastomers)	SS316L and SS316 (NACE MR 0175 compliance) SS316 Low temp.Nitrile(LNBR)- Std.
Operating Temperature Range(ambient) For Elastomers	Low temperature Nitrile : -60°C to +80°C (Std)
Standard Nominal Flow rate at 6bar(85 psi) supply pressure and 1 bar (14.5 psi) pressure drop (differential)	1/4" - 35 scfm (1000 slpm) (High flow version) 3/8" - 59 scfm (1680 slpm) (High flow version) 1/2" - 89 scfm (2520 slpm) (High flow version) 3/4" - 192 scfm (5428 slpm) (High flow version) 1" - 347 scfm (9820 slpm) (High flow version)
CV value	1/4" - 1.0 (High flow version) 3/8" - 1.70 (High flow version) 1/2" - 2.50 (High flow version) 3/4" - 5.40 (High flow version) 1" - 9.80 (High flow version)
Weight	1/4" 0.260 kg. 3/8" 0.770 kg. 1/2" 0.730 kg. 3/4" 2.500 kgs. 1" 2.860 kgs.



Note :


- 1) Lock Nut (hex nut) and spring will not have NACE MR 0175 compliance.
- 2) Internal 'wetted' parts will have NACE MR 0175 compliance.

+Values indicated are with 40 micron elements, with finer elements these values will be lower.

Flow Regulator Model SUDFR

SUDFR (1/4", 3/8", 1/2", 3/4", 1")

Option Selector



Flow Regulator Model SUDFR

SUDFR (1/4", 3/8", 1/2", 3/4", 1")

8 9 10 Test / Approval

A	0	0	ATEX
A	0	1	UKEX
A	0	2	UKCA
A	0	3	ATEX, UKEX, EAC Ex, UKCA
A	0	4	ATEX, UKEX, EAC Ex
A	0	5	ATEX, UKEX, UKCA
A	0	6	ATEX, UKEX, EAC Ex
B	0	0	ATEX, CE
B	0	1	ATEX, CE, UKEX, EAC Ex, UKCA
B	0	2	ATEX, CE, UKEX, EAC Ex
B	0	3	ATEX, CE, UKEX, UKCA
B	0	4	ATEX, CE, UKCA, EAC Ex
B	0	5	ATEX, CE, EAC Ex
C	0	0	CE
C	0	1	CE, UKEX, EAC Ex, UKCA
C	0	2	CE, UKEX, EAC Ex
C	0	3	CE, UKEX, UKCA
C	0	4	CE, EAC Ex, UKCA
C	0	5	CE, EAC EX
D	0	0	ATEX, EAC
D	0	1	ATEX, EAC, UKEX, EAC Ex, UKCA
D	0	2	ATEX, EAC, UKEX, EAC Ex
D	0	3	ATEX, EAC, UKEX, UKCA
D	0	4	ATEX, EAC, EAC Ex, UKCA
E	0	0	EAC
E	0	1	EAC, UKEX, EAC Ex, UKCA
E	0	2	EAC, UKEX, EAC Ex
E	0	3	EAC, UKEX, UKCA
E	0	4	EAC, EAC EX, UKCA
G	0	0	CE, EAC
G	0	1	CE, EAC, UKEX, EAC Ex, UKCA
G	0	2	CE, EAC, UKEX, EAC Ex
G	0	3	CE, EAC, UKEX, UKCA
G	0	4	CE, EAC, EAC Ex, UKCA
N	0	0	ATEX, CE, EAC
N	0	1	ATEX, CE, EAC, UKEX, EAC Ex, UKCA
N	0	2	ATEX, CE, EAC, UKEX, EAC Ex
N	0	3	ATEX, CE, EAC, UKEX, UKCA
N	0	4	ATEX, CE, EAC, EAC Ex, UKCA
[O]	[0]	[0]	Other customer special requirement if Any
Q	0	0	ATEX, EAC Ex
R	0	0	EAC Ex
R	0	1	EAC Ex, UKEX, UKCA
R	0	2	EAC Ex, UKCA
X	X	X	STANDARD UNITS WITHOUT ANY CERTIFICATE / APPROVAL

Flow Regulator Model SUDFR

SUDFR (1/4", 3/8", 1/2", 3/4", 1")

11 Material of Construction / Flow Capacity

H = High flow version - SS316L

12 13 14 Compliance

X	X	X	Standard Unit Without any Complinance
A	0	1	RoHS 3 Compliance
A	0	2	REACH Compliance
A	0	3	Copper Free (Only Applicable Aluminium Version)
A	0	4	RoHS3, REACH Compliance
A	0	5	RoHS3, REACH, Copper Free (Only Applicable for Aluminium Version)
A	0	6	RoHS3, Copper Free (Only Applicable for Aluminium Version)
A	0	7	REACH, Copper Free (Only Applicable for Aluminium Version)

Note : Option shown in the [] bracket are special, Please contact Sales HQ/Manufacturing.



Manderlay House
Manderlay Gardens
Emley
West Yorkshire
HD8 9TY

Email: enquiries@part-hunter.co.uk